What Is Claimed Is:

1. A method that facilitates dynamic delivery of service profiles to a client, comprising:

performing a discovery operation to allow the client to discover new services on a network;

if a new service is discovered for which the client does not possess a service profile, causing the client to obtain the service profile from the new service; and

causing the service profile to be installed on the client to enable the client to use the new service.

2. The method of claim 1, wherein causing the client to obtain the service profile involves:

causing the client to send a request for the service profile to the new service; and

causing the client to receive the service profile from the new service.

3. The method of claim 1, wherein the service profile includes code, and wherein causing the service profile to be installed on the client involves causing the code to be installed on the client.

4. The method of claim 1,

wherein the service profile includes a specification that describes how to use the new service; and

wherein causing the service profile to be installed on the client involves,

causing code to be generated to implement the specification, and

causing the code to be installed on the client.

5. The method of claim 1, wherein the service profile is encoded in a universal form that can be executed by different types of clients.

6. The method of claim 1,

wherein there exist different service profile implementations for different types of clients; and

wherein causing the client to obtain the service profile involves,

communicating characteristics of the client to the new service,

allowing the new service to select a service profile implementation for the client based on the characteristics of the client, and

allowing the new service to send the selected service profile implementation to the client.

7. The method of claim 1, wherein causing the client to obtain the service profile from the new service involves executing a dynamic extension profile, which implements a standard protocol that enables the client to acquire any profile the client needs at the time the profile is needed.

8. The method of claim 1,

wherein performing the discovery operation involves using the Bluetooth Service Discovery Protocol (SDP); and

wherein the client and the new service communicate using the Bluetooth networking standard.

9. The method of claim 1, wherein the service profile can define a service-specific Application Programming Interface (API).

10. The method of claim 1, wherein the service profile implements a domain-specific protocol stack associated with the new service.

11. A computer-readable storage medium storing instructions that when executed by a computer cause the computer to perform a method that facilitates dynamic delivery of service profiles to a client, the method comprising:

performing a discovery operation to allow the client to discover new services on a network;

if a new service is discovered for which the client does not possess a service profile, causing the client to obtain the service profile from the new service; and

causing the service profile to be installed on the client to enable the client to use the new service.

12. The computer-readable storage medium of claim 11, wherein causing the client to obtain the service profile involves:

causing the client to send a request for the service profile to the new service; and

causing the client to receive the service profile from the new service.

13. The computer-readable storage medium of claim 11, wherein the service profile includes code, and wherein causing the service profile to be installed on the client involves causing the code to be installed on the client.

14. The computer-readable storage medium of claim 11,

wherein the service profile includes a specification that describes how to use the new service; and

wherein causing the service profile to be installed on the client involves,

causing code to be generated to implement the specification, and

causing the code to be installed on the client.

15. The computer-readable storage medium of claim 11, wherein the service profile is encoded in a universal form that can be executed by different types of clients.

16. The computer-readable storage medium of claim 11,

wherein there exist different service profile implementations for different types of clients; and

wherein causing the client to obtain the service profile involves,

communicating characteristics of the client to the new service,

allowing the new service to select a service profile implementation for the client based on the characteristics of the client, and

allowing the new service to send the selected service profile implementation to the client.

17. The computer-readable storage medium of claim 11, wherein causing the client to obtain the service profile from the new service involves executing a dynamic extension profile, which implements a standard protocol that enables the client to acquire any profile the client needs at the time the profile is needed.

18. The computer-readable storage medium of claim 11,

wherein performing the discovery operation involves using the Bluetooth Service Discovery Protocol (SDP); and

wherein the client and the new service communicate using the Bluetooth networking standard.

19. The computer-readable storage medium of claim 11, wherein the service profile can define a service-specific Application Programming Interface (API).

20. The computer-readable storage medium of claim 11, wherein the service profile implements a domain-specific protocol stack associated with the new service.

21. An apparatus that facilitates dynamic delivery of service profiles to a client, comprising:

a discovery mechanism configured to perform a discovery operation that allows the client to discover new services on a network;

a profile transfer mechanism, wherein if a new service is discovered for which the client does not possess a service profile, the profile transfer mechanism

is configured to cause the service profile to be transferred from the new service to the client; and

an installation mechanism configured to cause the service profile to be installed on the client to enable the client to use the new service.

22. The apparatus of claim 21, wherein the profile transfer mechanism is configured to:

cause the client to send a request for the service profile to the new service; and to

cause the client to receive the service profile from the new service.

23. The apparatus of claim 21, wherein the service profile includes code, and wherein the installation mechanism is configured to cause the code to be installed on the client.

24. The apparatus of claim 21,

wherein the service profile includes a specification that describes how to use the new service; and

wherein the installation mechanism is configured to,

cause code to be generated to implement the specification, and to

cause the code to be installed on the client.

25. The apparatus of claim 21, wherein the service profile is encoded in a universal form that can be executed by different types of clients.

26. The apparatus of claim 21,

wherein there exist different service profile implementations for different types of clients; and

wherein the profile transfer mechanism is configured to,

communicate characteristics of the client to the new service,

allow the new service to select a service profile implementation for the client based on the characteristics of the client, and to

allow the new service to send the selected service profile implementation to the client.

27. The apparatus of claim 21, wherein the profile transfer mechanism is configured to execute a dynamic extension profile, which implements a standard protocol that enables the client to acquire any profile the client needs at the time the profile is needed.

28. The apparatus of claim 21,

wherein the discovery mechanism uses the Bluetooth Service Discovery Protocol (SDP); and

wherein the client and the new service communicate using the Bluetooth networking standard.

29. The apparatus of claim 21, wherein the service profile can define a service-specific Application Programming Interface (API).

30. The apparatus of claim 21, wherein the service profile implements a domain-specific protocol stack associated with the new service.

31. A device configured to dynamically deliver a service profile to a client to enable the client to use a service provided by the device, comprising:

the device configured to provide the service;

a memory within the device containing the service profile that enables clients to use the service provided by the device; and

a profile transfer mechanism configured to transfer the service profile to the client on demand.

32. The device of claim 31, further comprising a discovery mechanism configured to perform a discovery operation that allows devices to discover each other.